

Title:

L.M.I.G. / NON-L.M.I.G. ROADWAY RESURFACING BID FORM
(Submit an Original and Four Copies)

Line # & Pay Item #	Item Description	Unit of Measure	Approx. Qty	Unit Price (Dollars/Cents)	Bid Amount (Dollars/Cents)
<u>1</u> 432-5010	Mill Asphalt Concrete Existing Pavement at project limits, curb & gutter and side roads as required by The City of Auburn. Mill depth to be variable. (Sixth Avenue)	SQUARE YARD	1,500		
<u>2</u> 432-5010	Mill Asphalt Concrete Existing Pavement. Mill Depth is approximately 1 to 2 inches. Set Existing Graded Aggregate Base. (Pointers Way cul-de-sac)	SQUARE YARD	580		
<u>3</u> 301-1000	Full Depth Reclamation with Portland Cement, including: pulverization/recycling of existing soil/crushed stone base and existing asphalt pavement materials. Recycle depth to be 8" inches. Reconstruction to include reshaping, grading, proper compaction, and curing. 40 lbs/yd ² of Portland Cement to be used. Bituminous Prime Coat included. (Dogwood Lane, Pinetree Lane & River Oaks)	SQUARE YARD	4,340		
<u>4</u> 415-0000	Recycled Asphaltic Concrete Open Graded Crack Relief Interlayer (OGI), including Bituminous Materials, Hydrated Lime and Haul. 110 lbs/yd ² . (Sixth Avenue)	TON	350		
<u>5</u> 402-3190	Recycled Asphaltic Concrete 19 MM Superpave, Group 1 or 2, Including Bituminous Material, Hydrated Lime & Haul. 220 lbs/yd ² . (Pointers Way cul-de-sac)	TON	65		
<u>6</u> 402-3130	Recycled Asphaltic Concrete 12.5 MM Superpave Wearing Course, Group 2 Only , including Bituminous Material, Hydrated Lime and Haul. 165 lbs/yd ² . (Sixth Avenue)	TON	520		

L.M.I.G. / NON-L.M.I.G. ROADWAY RESURFACING BID FORM
(Submit an Original and Four Copies)

<u>7</u> 402-3147	Recycled Asphaltic Concrete 12.5 MM Superpave Wearing Course, Blend 1 , including Bituminous Material, Hydrated Lime and Haul. 220 / 165 lbs/yd ² . (Dogwood Lane, Pinetree Lane, River Oaks & Pointers Way Cul-de-sac)	TON	560		
<u>8</u> 413-1000	Bituminous Tack Coat	GALLONS	1,095		
<u>9</u> 653-1501	Solid Traffic Stripe, 5" (inch), White, Standard Thermoplastic (Sixth Avenue)	LINEAR FOOT	3,600		
<u>10</u> 653-1502	Solid Traffic Stripe, 5"(inch), Yellow, Standard Thermoplastic (Sixth Avenue)	LINEAR FOOT	3,600		
<u>11</u> 653-1704	Solid Traffic Stripe, 24"(inch), White, Standard Thermoplastic	LINEAR FOOT	170		
<u>12</u> 653-0230	Pavement Marking Word, Type 3A, "SCHOOL", White, Standard Thermoplastic (Sixth Avenue)	EACH	3		
<u>13</u> 210-0200 706-0000	Shoulder Re-Construction and Turf Establishment	SHOULDER MILE	1.26		
<u>14</u> 150-1000	Traffic Control	LUMP	100 %		
<u>15</u> 999-8004	Testing Core Samples – Asphaltic Concrete	EACH	5		
	TOTAL BID				