

ROADWAY SUMMARY
(PAGE 1 OF 1)

DOGWOOD LANE

L.M.I.G.

City of Auburn

From: Greentree Drive

To: Dead End at Cul-de-sac

450 Lin. Ft. 0.08 Mile 20' Wide Pavement (no curb & gutter)
21' Wide Full Depth Reclamation (6" wider each side
of new pavement edge)

<u>ITEM</u>	<u>UNIT OF MEASURE</u>	<u>APPROX. QUANTITY</u>
Full Depth Reclamation with Portland Cement, Including pulverization/recycling of existing soil/ crushed stone base and existing asphalt pavement materials. Recycle depth to be 8" inches. Reconstruction to include reshaping, grading, proper compaction and curing. 40 lbs/yd ² of Portland Cement to be used. Bituminous Prime Coat included.	SQUARE YARD	1,560
Recycled Asphaltic Concrete 12.5 MM Superpave wearing course, Blend 1, Including Bituminous Material, Hydrated Lime & Haul. 220 lbs/yd ² .	TON	180
Bituminous Tack Coat	GALLONS	110
Solid Traffic Stripe, 24" (inch), White, Standard Thermoplastic	LINEAR FOOT	10
Shoulder Re-Construction & Turf Establishment	SHOULDER MILE	0.19
Traffic Control	LUMP	100 %
Asphaltic Concrete Testing (To include Asphaltic Concrete Core Samples)	EACH	1